

MOISTURE ANALYZER ANA21-110C



MOISTURE ANALYZER ANA21-110C

Moisture Analyzer measures the amount of moisture in a substance which particularly helps in food processing. These analyzers are also commonly used in environmental, pharmaceutical, and materials science labs. We provide a variety of moisture analyzer according to applications, features and customers requirements.

Used in Food processing, Environmental, Pharmaceutical, Laboratory, Research, Medical, Hospitals, Agriculture, Industrial.

Also known as Laboratory Moisture Analyzer, Moisture Balance, Moisture Meter, Halogen Moisture analyzer, Laboratory Moisture Balance, Laboratory moisture Meter, Laboratory Halogen Moisture analyzer.

ANA21-110C MOISTURE ANALYZER

Halogen Heating

Pan size: \varnothing 100mm

3.7 inch touch screen

Long distance operated

Stainless steel chamber

Easy cleaning after testing

Temperature and time can be set

The percentage of moisture content

Max 230 degree heating temperature

Automatic opens the heating chamber



SPECIFICATIONS

| | |
|-----------------------------|------------------------|
| Model | ANA21-110C |
| Weighing Range | 110 g |
| Temperature | 40°C-230°C |
| Operating Temperature Range | 5°C-35°C |
| Temperature Set | 1°C |
| Temperature Setting | 40°C-230°C By 1°C Step |
| Moisture Range | 0.00%-100.0% |
| Moisture Readability | 0.0001 |
| Dry Range | 100.00%-0.00% |
| Dry Residual Readability | 0.0001 |
| Pan Size | Φ 100 mm |
| Readability | 0.001 g |
| Interface | Cable, RS232/RJ45/USB |
| Heat Source | HALOGEN LAMP |
| Calibration | External Calibration |
| Rechargeable Battery | No |
| Temperature Sensor | PT-100 |
| Display | 7 inch touch panel |
| Operation Height | 275 mm |
| The Chamber Height | 35 mm |
| Time Setting | 1-99 min By 10 s |

| | |
|---------------------|---------------------------------------|
| Dimension | 215x195x415 mm |
| Indicator Dimension | 200x75x135 mm |
| Number of History | 20 |
| Number of Storage | 20 |
| Power | 400 W |
| Balance | Output: 9 V |
| Machine | Output: 24 V (Dual-drive) |
| Power Supply | 220 V± 15%, 110 V± 15% / 50 Hz, 60 Hz |

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com