

MICROBIOLOGICAL INCUBATOR INC63-400



MICROBIOLOGICAL INCUBATOR INC63-400

Microbiological Incubator can be used for many applications beyond traditional bacterial culture, such as temperature dependent incubations, enzymatic reactions or for reagent storage. Programmable controls and refrigeration are some of the additional features available in incubators on the market today.

Used in Temperature dependent incubations, Enzymatic reactions, Reagent Storage. Programmable controls, Refrigeration.

Also known as Laboratory Microbiological Incubator.

INC63-400 MICROBIOLOGICAL INCUBATOR

ALLCOLD Refrigeration Technology: Auto defrost, multiple security system, long time running, environmental protection, high efficiency and energy saving, Auto-defrost function, Imported DuPont SUVA R134 a environmental refrigerant.

ALLFLOW Perfect Air Current Cycling: Perfect forced convection, maximum number of working room, minimum temperature recovery time after the opening, world famous axial fan, perfect air current design.

ALLSENS Programmable PID Control: Adaptive PID controller precisely controls the temperature and humidity, prevent temperature soaring, keep working room temperature stable and uniformity.

Excellent Imported temperature and humidity Sensor.

Efficient isolation Design



SPECIFICATIONS

Model	INC63-400
Capacity	400 L
Temperature Range	0-65°C
Ambient Temperature	10~30°C
Temperature Fluctuation	±0.5°C
Temperature Uniformity	±1.5
Temperature Resolution	0.1°C
Ambient Humidity	<70%
Timer Range	0-99 hrs, 0-9999 min, can be chose
Convection Mode	Forced Convection
Internal Dimention (WxDxH)	600x640x1050 mm
Overall Dimension (WxDxH)	745x930x1700 mm
Package Size	1907x815x1090 mm
Shelves/Trays	4
Weight	158/158 kg
Power	1100 W
Power Supply	Single phase AC220 V/50 Hz

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com