

-10°C TO -40°C ULTRA LOW TEMPERATURE FREEZER ULT23-936



-10°C TO -40°C ULTRA LOW TEMPERATURE FREEZER ULT23-936

Innovative design and highly efficient for the user to use them for storing laboratory materials such as vaccines, biological samples, enzymes and protein samples. Excellent temperature uniformity, reliable environment monitoring and rust free construction supports this product to become an ideal choice.

Used in Routine Cold Storage, Laboratories, Biologicals, Pharmaceuticals, Clinical, Research.

Also known as Laboratory ULT freezer, ULT Freezer, Ultra-low Freezer.

ULT23-936 -10°C TO -40°C ULTRA LOW TEMPERATURE FREEZER

LED digital display and increment at 0.1°C

Permanently lubricated cooling fan for safety and longevity

Independent inner door to avoid more cooling leaking out, and provide more stable inside temperature performance

High density CFC-Free urethane foam insulation

Build-in lock with safety

Lockable caster design

Chemically stable, CFC -free, commercially available and environmentally safe refrigerant

Optimized refrigeration system designed to maximize cooling effect and temperature uniformity

Visible and Audible alarm

Corrosion proof cabinet interior design

Power failure protect: the device would be attack by the high current when all devices restart simultaneously, the start-delay function would protect device from the damage



SPECIFICATIONS

Model	ULT23-936
Capacity	936 L
Temperature Range	-25°C to -40°C
Ambient Temperature	10°C ~ +32°C
Defrosting	Manual
Cooling Type	Direct Cooling
Insulation Material	PURF
Refrigerant	Mixed-gas
Internal Dimension	1000x700x1335 mm
Overall Dimension	1304x1000x2017 mm
Package Size	1350x1080x2150 mm
Drawers/Shelves	Shelves
Interior	Stainless steel
Exterior	Color sprayed steel
Controller	Microprocessor, Digital display
Sensor	PTC
Compressor Brand/QTY	SECOP/1

Condenser	Copper tube and finned
Noise Level	50 db
Alarm	High/low temperature, Power failure, Sensor malfunction, Filter screen check, Temperature controller malfunction, Low battery, Condenser clean, High ambient temperature, Door ajar
Standard Accessories	Castor, Inner door, Test hole 1/18 mm, Remote alarm port, USB port
Optional Accessories	USB data logging, Temperature recorder
Weight (Net/Gross)	310/330 kg
Rated Power	1000 W
Power Consumption (Kwh/24hrs)	14.5
Rated Current A	5.8 A
Power Supply	220 V, 50 Hz

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com