



HORIZONTAL AUTOCLAVE AUT22-0100B

Laboratory horizontal autoclaves are useful in bulk sterilization applications of equipment and materials in various industries and research institutions. Also for disposing biological waste, reducing the risk of contamination and sterile the waste before discarding. We provide a variety of horizontal autoclave according to applications, features and customers requirements.

Used in Bulk sterilization, Microbiology Lab, Research Institutions, Laboratory, Pharmaceutical, Food industry, Chemical industry.

Also known as Laboratory Sterilizer, Horizontal Pressure Sterilizer, Laboratory Horizontal Autoclave,.

AUT22-0100B HORIZONTAL AUTOCLAVE

Sterilizing programs for fabric, instrument, rubber and liquid Touch screen display of temperature, pressure, time, running status and failure warning

Post-dying function makes the residual humidity of sterilized articles less than 3% The positive pressure air-exhaust system to exhaust the cold air from chamber Equipped with printer to print date, time and process parameters Build-in efficient steam generator, microcomputer temperature control Perfect four-level authority management system to avoid misoperation Double door optional



SPECIFICATIONS

Model	AUT22-0100B
Capacity	100 L
Chamber Size	Ф400x 850 mm
Chamber Material	SUS304
Max Working Pressure	0.23 Mpa
Working Temp.	115-138°C
Temperature Accuracy	+0.1° C
Consumption	10 KW
Power Supply	380 V, 50 HZ
External Size(LxWxH)	1250x730x1660 mm
Package Size(LxWxH)	1500x900x2050 mm
Gross Weight	310 kg



Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@centrifugen.com | Website: centrifugen.com