



## HORIZONTAL AUTOCLAVE AUT22-0150

Laboratory horizontal autoclaves are useful in bulk sterilization applications of equipment and materials in various industries and research institutions. Also for disposing biological waste, reducing the risk of contamination and sterile the waste before discarding. We provide a variety of horizontal autoclave according to applications, features and customers requirements.

Used in Bulk sterilization, Microbiology Lab, Research Institutions, Laboratory, Pharmaceutical, Food industry, Chemical industry.

Also known as Laboratory Sterilizer, Horizontal Pressure Sterilizer, Laboratory Horizontal Autoclave,.

## **AUT22-0150 HORIZONTAL AUTOCLAVE**

Drying function
Automatic sterilization process
Safety valve for over pressure protection
Over-temperature, over-pressure protection device
304 stainless steel material chamber
Automatically in case of low water level.
4 Water level sensor. The power will be cut-off
Double door optional
Interlock function



**Product Image Coming Soon** 

## **SPECIFICATIONS**

Model	AUT22-0150
Capacity	150 L
Chamber Size	Ф440x1000 mm
Working Pressure	0.22 Mpa
Working Temp.	134 °C
Temperature Range	105-134°C
Sterilization Time	0-60 min
Drying Time	0-60 min
Temp. Display Accuracy	≤±2°C
Consumption	9 KW
Power Supply	220 V/380 V, 50/60 Hz
External Size (W*D*H)	1400x600x1300 mm
Package Size (W*D*H)	1550x750x1850 mm
Gross Weight	320 kg



## Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@centrifugen.com | Website: centrifugen.com