

HORIZONTAL AUTOCLAVE AUT22-0200



HORIZONTAL AUTOCLAVE AUT22-0200

Laboratory horizontal autoclaves are useful in bulk sterilization applications of equipment and materials in various industries and research institutions. Also for disposing biological waste, reducing the risk of contamination and sterile the waste before discarding. We provide a variety of horizontal autoclave according to applications, features and customers requirements.

Used in Bulk sterilization, Microbiology Lab, Research Institutions, Laboratory, Pharmaceutical, Food industry, Chemical industry.

Also known as Laboratory Sterilizer, Horizontal Pressure Sterilizer, Laboratory Horizontal Autoclave,.

AUT22-0200 HORIZONTAL AUTOCLAVE

- Drying function
- Automatic sterilization process
- Safety valve for over pressure protection
- Over-temperature, over-pressure protection device
- 304 stainless steel material chamber
- Automatically in case of low water level.
- 4 Water level sensor. The power will be cut-off
- Double door optional
- Interlock function



Product Image Coming Soon

SPECIFICATIONS

Model	AUT22-0200
Capacity	200 L
Chamber Size	Φ515x1000 mm
Working Pressure	0.22 Mpa
Working Temp.	134 °C
Temperature Range	105-134°C
Sterilization Time	0-60 min
Drying Time	0-60 min
Temp. Display Accuracy	±2°C
Consumption	9 KW
Power Supply	220 V/380 V, 50/60 Hz
External Size (W*D*H)	1400x670x1650 mm
Package Size (W*D*H)	1560x820x1850 mm
Gross Weight	350 kg

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com