

THERMOSTATIC OIL BATH BAC51-10



THERMOSTATIC OIL BATH BAC51-10

They are suitable for jacketed reactor and also have the intelligent control system. Optional water circulation cooling device which can be used to attain the rapid cooling while controlling the high temperature in the exothermic reaction. It is specifically used for calibration tests, high temperature organic distillation, external circulation and high temperature experiments in all types of industries.

Used in Immunoassays, Melting points, Enzyme reactions, Boiling points, Incubation, Activation of cultures, Laboratory procedures..

Also known as Digital Dry Bath Incubator, Heating block, Laboratory Dry Bath Incubator.

BAC51-10 THERMOSTATIC OIL BATH



SPECIFICATIONS

Model	BAC51-10
Temperature Range	RT~100°C
Temperature Fluctuation	±0.1°C
Pump Flow Rate	8 L / min
Inner Dimension (WxDxH)	200x250x200 mm
Power Supply	220 V

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52215	Block	1.5/2.0ml adaptors (6/pack)
LS52228	Block	0.2 mL 24-well Block
LS52241	Block	0.5 mL 12-well Block
LS52254	Block	1.5 mL 6-well Block

Accessory Code	Name	Description
LS52267	Block	2.0 mL 6-well Block
LS52280	Block	15 mL 6-well Block
LS52293	Block	50 mL 3-well Block
LS52306	Block	96-well/Flat Bottom Block

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com