# AIR COOLED CHILLER CHI21-019



# AIR COOLED CHILLER CHI21-019

Air cooled chiller absorb heat from process water, and the heat is then transferred to the air around the chiller unit. Air cooled chiller require less maintenance.

Used in Laboratory, Pharmaceutical, Chemical, Laser.

Also known as Laboratory Air Cooled Chiller.

### CHI21-019 AIR COOLED CHILLER

It adopts single-stage vapor compression circuit and has compressor overload protection, pump overload protection, reverse phase and lack of phase warning, anticing protection, high and low pressure protection and other devices.

The machine has stable performance and long life.

It can cool down quickly, and the temperature is stable to meet customer requirements.

This series of products mainly work on the principle of cold and heat exchange.

It is suitable for the cooling field in modern industry and is not affected by the ambient temperature.

It is an indispensable configuration device.



### **SPECIFICATIONS**

Model	CHI21-019
Freezing capacity	
kw	19.9 kw
kcal/h	17114 kcal/h
btu/h	67898.8 btu/h
Compressor	
Output power	6 kw
hp	4x2 hp
Weight	7 kg
Refrigerant	
Control mode	Thermostatic expansion valve
Туре	R22 ( R407C optional )
Evaporator(Type)	Tube-in-shell
Condenser(Air Chiller)	
Fan power	0.45x2
Туре	High effective inner threaded copper finned + low noise fan
Water tank capacity	120 L
Pump	
Туре	Stainless steel centrifugal pump
Power kw	0.75 kw
Flow rate	115 l/min
Working pressure	2 bar
Chilled wateroutlet	1 v 2 inchx1
Pipe coupling	

Chilled water inlet	1 v 2 inchx1
Water tank drainage port	1/2 inch
Dimension(LXWXH) mm	1590x700x1330 mm
Weight	320 kg
Power	3 ph-380 V/50 Hz (220 V/400 V/415 V/440 V 50 Hz/60 Hz)
Temperature	5-35 ℃
Tolerance	± 0.5 °C (± 1 °C at low load)
Safety protections	High and low pressure controller/anti-freezing switch/overload of pump and compressor protection/overheat protection/delayed protection



## Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@centrifugen.com | Website: centrifugen.com