STANDARD FUME HOOD FUH13-1200

444

centrifugen.com

STANDARD FUME HOOD FUH13-1200

Created to provide protection from toxic fumes and hazardous volatile vapours, and are reliable and easy to use. Inbuilt ventilation system lowers the risk of fire and explosion. For metal analysis, pharmacy and research field along with safety measures, this product becomes unique choice for the buyers to purchase according to their needs.

Used in Metal analysis, Pharmacy, Research Field, Commercial, Medical, Laboratory.

Also known as Standard Fume Hood, Laboratory Fume Hood, Chemical Fume Hood.

FUH13-1200 STANDARD FUME HOOD

Microprocessor control system, LED display Made of porcelain white PP, Resistant to acid, alkali and anti-corrosion With memory function in case of power-failure Manual front glass window, height adjustable Built-in PP centrifugal blower; low noise, easy installation Chemical resistant phenolic resin work table Optional: PP work table, epoxy resin board or ceramic board



SPECIFICATIONS

| Model | FUH13-1200 |
|-----------------------------|---|
| Airflow Velocity | 0.3~0.8 m/s |
| Max Opening | 740 mm |
| Length | 1200 mm |
| LED Lamp | 30Wx1 |
| Front Window | Manual, Resistant to acid and alkali, 5 mm toughened glass, height adjustable |
| Blower Optional Choice | Built-in PP centrifugal blowers, Speed adjustable |
| Standard Accessory | Illuminating lamp, Water tap, Water Sink, Base cabinet waterproof socket*2, 4 meters PVC duct, Diameter: 250 mm, PP centrifugal Blower, Pipe strap*2 |
| Work Surface Height | 820 mm |
| Inner Dimension | 980x570x700 mm |
| Overall Dimension | 1240x800x2450 mm |
| Package Size (Main Body) | 1390x940x1620 mm |
| Package Size (Base Cabinet) | 1390x940x1040 mm |
| Noise Level | ≤68 dB (A) |
| Weight (Net/Gross) | 198 kg |
| Power | 360 W |
| Power Supply | 220V ±10%, 60/50Hz; 110V ±10%, 60Hz |



Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@centrifugen.com | Website: centrifugen.com