STANDARD FUME HOOD FUH13-1500



STANDARD FUME HOOD FUH13-1500

Created to provide protection from toxic fumes and hazardous volatile vapours, and are reliable and easy to use. Inbuilt ventilation system lowers the risk of fire and explosion. For metal analysis, pharmacy and research field along with safety measures, this product becomes unique choice for the buyers to purchase according to their needs.

Used in Metal analysis, Pharmacy, Research Field, Commercial, Medical, Laboratory.

Also known as Standard Fume Hood, Laboratory Fume Hood, Chemical Fume Hood.

FUH13-1500 STANDARD FUME HOOD

Microprocessor control system, LED display

Made of porcelain white PP, Resistant to acid, alkali and anti-corrosion

With memory function in case of power-failure

Manual front glass window, height adjustable

Built-in PP centrifugal blower; low noise, easy installation

Chemical resistant phenolic resin work table

Optional: PP work table, epoxy resin board or ceramic board



SPECIFICATIONS

Model	FUH13-1500
Airflow Velocity	0.3~0.8 m/s
Max Opening	740 mm
Length	1500 mm
LED Lamp	30Wx2
Front Window	Manual, Resistant to acid and alkali, 5 mm toughened glass, height adjustable
Blower Optional Choice	Built-in PP centrifugal blowers, Speed adjustable
Standard Accessory	Illuminating lamp, Water tap, Water Sink, Base cabinet waterproof socket*2, 4 meters PVC duct, Diameter: 250 mm, PP centrifugal Blower, Pipe strap*2
Work Surface Height	820 mm
Inner Dimension	1280x570x700 mm
Overall Dimension	1540x800x2450 mm
Package Size (Main Body)	1690x940x1620 mm
Package Size (Base Cabinet)	1690x940x1040 mm
Noise Level	≤68 dB (A)
Weight (Net/Gross)	225 kg
Power	360 W
Power Supply	220V ±10%, 60/50Hz; 110V ±10%, 60Hz



Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@centrifugen.com | Website: centrifugen.com