



AUTOMATIC AIR GENERATOR GEN12-5000

Air Generator is designed for removing hydrocarbons from the air stream and produces pure, hydrocarbon free and dry air, with a very low dew point. Long service life, easy maintenance, abrasion resistant, cost effective, performance, quick and easy servicing are some of the features which makes it convenient for the laboratory.

Used in Pharmaceutical, Gas Chromatography Detectors, Petrochemical, Laboratory, Medical, Research, Industries, Environmental, Clinical, Forensics..

Also known as Laboratory Air Generator.

GEN12-5000 AUTOMATIC AIR GENERATOR

High precision output pressure

Water automatically drain out

Two levels stainless steel made purifications

Large inside stainless steel air tank

Have two levels pressure stable valve. Output air pressure much stable

Have over pressure protection, low voltage start up, DC, greatly protect inside compressor



SPECIFICATIONS

Model	GEN12-5000
Environmental Temperature	0-45°C
Humidity	<85%
Flow Rate	0-5000 ml / min
Output Pressure	0-0.4 Mpa
Pressure Stability	<0.003 Mpa
Noise	<35 dB (A)
Dimension	480x260x350 mm
Net Weight	22 kg
Consumption Power	250 W
Power Supply	220 V±10% V



Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@centrifugen.com | Website: centrifugen.com