

BIOLOGICAL INDICATOR INCUBATOR INC51-100



BIOLOGICAL INDICATOR INCUBATOR INC51-100

Biological Indicator Incubator is supporting equipment for bio-indicator. It is small in size, less weight and is suitable for pressure steam sterilizer biological indicator, ethylene oxide sterilization biological indicator and other biological indicator sterilization, effect detection and cultivation.

Used in Environmental protection, Research institutes, University laboratories.

Also known as Laboratory Incubator.

INC51-100 BIOLOGICAL INDICATOR INCUBATOR

Unique designed. Small size, light weight, portable, and suits on various occasions.

LCD display. Temperature and time display simultaneously.

Auto fault detect and buzzer alarm. Temperature calibration function.

24V DC power supply input, low energy consumption. Built-in over-temperature protection device, safe and reliable.

Timing function. Time range from 0 to 999 min.

Variety of standard sample blocks for choice. Convenient for replacement. Block can be customized.



SPECIFICATIONS

Model	INC51-100
Temperature Range	RT+5°C~100°C
Temperature Accuracy	±0.5°C at 56°C
Display Accuracy	0.1°C
Time for Heating	≤6 min (20°C to 56°C)
Timer Range	1 sec~999 sec or 1 min~999 min
Overall Dimension (WxDxH)	110x156x92 mm
Weight	1 kg
Power	60 W
Power Supply	DC 24 V adapter

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS54430	Block A	15 x Φ10 mm
LS54442	Block B	12 x Φ12 mm
LS54454	Block C	6 x Φ15 mm
LS54466	Block D	6 x Φ16 mm
LS54478	Block E	18 x Φ 9 mm
LS54814	customized	

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com