

# MICROBIOLOGICAL INCUBATOR INC64-400



# MICROBIOLOGICAL INCUBATOR INC64-400

Microbiological Incubator can be used for many applications beyond traditional bacterial culture, such as temperature dependent incubations, enzymatic reactions or for reagent storage. Programmable controls and refrigeration are some of the additional features available in incubators on the market today.

Used in Temperature dependent incubations, Enzymatic reactions, Reagent Storage. Programmable controls, Refrigeration.

Also known as Laboratory Microbiological Incubator.

## INC64-400 MICROBIOLOGICAL INCUBATOR

ALLCOLD Refrigeration Technology: Auto defrost, multiple security system, long time running, environmental protection, high efficiency and energy saving, Auto-defrost function, Imported DuPont SUVA R134 a environmental refrigerant.

ALLGENT Humidification System: Automatic water intake, automatic water level control, persistent

ALLFLOW Perfect Air Current Cycling: Perfect forced convection, maximum number of working room, minimum temperature recovery time after the opening, world famous axial fan, perfect air current design.

ALLSENS Programmable PID Control: Adaptive PID controller precisely controls the temperature and humidity, prevent temperature soaring, keep working room temperature stable and uniformity.

Excellent Imported temperature and humidity Sensor.

Efficient isolation Design



## SPECIFICATIONS

Model	INC64-400
Capacity	400 L
Temperature Range	0-65°C
Ambient Temperature	10~30°C
Temperature Fluctuation	±0.5 at 10-40°C
Temperature Uniformity	±1.5
Temperature Resolution	0.1°C
Relative Humidity	Below 70%
Sterilization Function	Yes
Humidity Range	40-95 %RH
Humidity Fluctuation	±2 RH
Interior	SUS304 Stainless Steel Materials
Heat insulator material	Imported environmental protection material
Timer Range	0-99 hrs, 0-9999 min
Convection Mode	Forced Convection
Internal Dimention (WxDxH)	601x639x1052 mm
Overall Dimension (WxDxH)	745x930x1700 mm
Package Size	815x1090x1907 mm
Shelves/Trays	4
Weight	158.5/188 kg
Power	1350 W

Power Supply	Single phase AC220 V/50 Hz
--------------	----------------------------

***Centrifugen***

**Centrifugen**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [info@centrifugen.com](mailto:info@centrifugen.com) | Website: [centrifugen.com](http://centrifugen.com)