AIR JACKETED CO2 INCUBATOR INC92-080

<u>aaaa</u>a

centrifugen.com

AIR JACKETED CO2 INCUBATOR INC92-080

Precise management of temperature and CO2 provides an exceptionally stable environment, it is easy to maintain precise time/date stamped records of all incubator functions as often as necessary and adopts door heating control system. It is majorly used in issue engineering, mammalian cell research, tissue culturing and oncology studies. Used in Cell Culturing, Tissue culturing, Tissue Engineering, Vitro fertilization, Mammalian cell research, Oncology studies..

Also known as Laboratory CO2 Incubator Air Jacketed.

INC92-080 AIR JACKETED CO2 INCUBATOR

Forced Convection Inner material: SUS304 stainless steel ALLHEATTM:Chamber Preheating Technology ALLFLOWTM:Clean Air Circulation System ALLSENSTM:Programmable PID Controller



SPECIFICATIONS

Model	INC92-080
Capacity	80 L
Temperature Range	RT+5~55°C
Ambient Temperature	10~30°C
Temperature Accuracy	0.1°C
Temperature Fluctuation	±0.5 at 37°C
Temperature Uniformity	±0.8 at 37°C
Temperature Recovery Time	(after 30 seconds door opening to 37° C) $\leq 8 \text{ min}$
Ambient Humidity	<70%
CO2 Range	0~20%
CO2 Sensor	IR sensor (±0.1%)
CO2 Recovery Time	(after 30 seconds door opening to 5%) ≤2 min
Filter	None
Humidifying Method	Natural Evaporation
Jacket Type	Water Jacketed
Internal Dimention (WxDxH)	500x400x400 mm
Overall Dimension (WxDxH)	755x550x547 mm
Shelves	2
Weight	35 kg
Power	500 W
Power Supply	Single phase AC220V/50Hz



Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@centrifugen.com | Website: centrifugen.com