AIR JACKETED CO2 INCUBATOR INC94-240

<u>aaaa</u>a

-

centrifugen.com

AIR JACKETED CO2 INCUBATOR INC94-240

Precise management of temperature and CO2 provides an exceptionally stable environment, it is easy to maintain precise time/date stamped records of all incubator functions as often as necessary and adopts door heating control system. It is majorly used in issue engineering, mammalian cell research, tissue culturing and oncology studies. Used in Cell Culturing, Tissue culturing, Tissue Engineering, Vitro fertilization, Mammalian cell research, Oncology studies..

Also known as Laboratory CO2 Incubator Air Jacketed.

INC94-240 AIR JACKETED CO2 INCUBATOR

151 liters internal volume Zironuim oxide Sensor IR CO2 sensor Water Level Alarm Integrated electric siphon pump Auto-zero Temperature deviation (at 37° C) Moist-heat disinfection at 90°C Relative humidity ≥95%



SPECIFICATIONS

Model	INC94-240		
Capacity	240 L		
Temperature Range	5°C above ambient temperature to 50°C		
Temperature Stability	±0.1°C		
Temperature Uniformity	±0.2°C		
CO2 Range	0-20%		
CO2 Stability	±0.1%		
CO2 Sensor	Thermal Conductivity		
CO2 Inlet Pressure	0.1 Mpa		
Filter	0.3 um, Efficiency:99.998% (for CO2)		
Access Port	Standard		
Remote alarm contacts	Standard		
Relative Humidity	≥ 95%		
Humidifying System	Special designed water reservoir		
Water reservoir volume	3 L		
Inner Door	6 inner doors standard		
Interior	Type 304, mirror finish, stainless steel		
Exterior	Electrolyzed galvanization steel, powder coated		
Temperature Sensors	PT1000		
Internal Dimention (WxDxH)	607x580x670 mm		
Overall Dimension (WxDxH)	780x820x944 mm		
Shelves/Trays	3 standard, 12 maximum		

Shelf Dimension(WxD)	423×445 mm			
Temperature control method	l Microprocessor			
CO2 control system	Microprocessor			
Alarm System	Power interruption, High/Low temperature, Deviation of CO2, RH, Door ajar, Independent overheat protection			
Weight	80 kg			
Data Output	RS232			
De-contamination	90°C moist heat disinfection			
Power	735 W			
Power Supply	AC-220 V/AC 110 V 50/60 Hz			

ACCESSORIES

Accessory Code	Name	Description	3 Sets	1 Set
LS53974	Standard shelf		3 Sets	
LS53986	Electric siphon pump			1 Set

Description

High 200 mm without castor

High 600 mm with castor

OPTIONAL ACCESSORIES

Accessory Code		Description	Accessory Code	Name	
LS53650	Air connector		Code		
LS53674	Electric siphon pump		LS53854	Floor stand for 2 stacked incubators	
LS53710	10 Small CO2 inlet filter				
LS53758	8 CO2 regulator		LS53914	Floor stand for 1 incubator	
LS53842	Shelf	Including :shelfx1, shelf supportx2	LS53950	4 in 1 CO2 steel cylinder auto-switch device	
			LS53962	CO2 steel cylinder auto- switch device	



Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@centrifugen.com | Website: centrifugen.com