VORTEX MIXER MIX37-25



VORTEX MIXER MIX37-25

Constructed of rugged, corrosion-resistant materials, the instruments endure heavy everyday usage. The ergonomic low profile design makes everyday vortexing comfortable for the user. Unnecessary movement has been avoided during use due to robust die-cast body.

Used in Mixing, Laboratory, Research, Medical.

Also known as Laboratory Vortex Mixer.

MIX37-25 VORTEX MIXER

Touch operation or continuous mode
Used for various mixing applications with optional adapters
Various adapters fit for different tubes
Specially designed vacuum suction foot for body stability
Robust aluminum-cast construction



SPECIFICATIONS

Model	MIX37-25	
Speed Range	25000 rpm	
Permissible Ambient Temperature	5-40°C	
Permissible Relative Humidity	80% RH	
Orbital Diameter	4 mm	
53	Motor rating output [W]	
Operation	Continuous/ touch operation	
Overall Dimension	127W×130H×160Dmm	
Motor Type	Shaded pole motor	
Protection Class	IP21	
Weight	3.5 kg	
Power	60 W	
Power Supply	110-120 V/220-230 V, 50/60 Hz	

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS52332	Rubber vacuum suction foot with screw, 1pc	
LS52371	Platform pad	For <Ø99mm tubes and small vessels

Accessory Code	Name	Description
LS52462	Tube adapter	For 12 holes test tubes, Ø12mm , used with MX1027/ MX1026/PS1.1
LS52475	Tube adapter	For 8 holes test tubes, Ø16mm, used with MX1027/ MX1026/PS1.1

LS52384	Standard top cup	For <Ø30mm tubes and small vessels
LS52436	Tube adapter	For 48 holes test tubes, Ø6mm, used with MX1027/ MX1026/PS1.1
LS52449	Tube adapter	For 15 holes test tubes, Ø10mm, used with MX1027/ MX1026/PS1.1

LS52	2488	Tube adapter	For 8 holes test tubes, Ø20mm, used with MX1027/ MX1026/PS1.1
LS52	2501	Universal top plate	100mm plate attachment , free of Rubber vacuum suction foot (18900158, 4pcs)
LS52	2527	Tube holding rod	Used with MX1028 to MX1032



Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@centrifugen.com | Website: centrifugen.com