METALLURGICAL MICROSCOPE MSC31-500D

<u>aaaa</u>a

centrifugen.com

METALLURGICAL MICROSCOPE MSC31-500D

Metallurgical Microscope is a specialized microscope designed for looking at cross-sections of metal targets , these are employed with high-resolution objective lenses with very short working distances and are usually inverted. Used in Biological and Chemical Laboratory, Pharmaceutical, Food industry, Medical, Research Institutes, University.

MSC31-500D METALLURGICAL MICROSCOPE

Excellent optical function with infinite optical system.

Innovative stand structure and sharp image display.

Convenient operation and special design for viewing incubating cell tissue. Valid mould proof design.

It can be used under the high temperature and high humidity environment.



SPECIFICATIONS

| Model | MSC31-500D |
|---|-----------------|
| Optical System | |
| Infinite optical system | Standard outfit |
| Extra Wide Field Eyepiece | |
| EW10 x/ 22 | Standard outfit |
| EW10 x/20 eyepiece with scale of cross hair | Standard outfit |
| EW15 x/ 16 | Optional |
| EW20 x/12 | Optional |
| Infinite LWD Plan Achromatic Objective | |
| 5x /0.12 /∞ /0 (BF/DF) LWD 10 mm | Standard Outfit |
| 10x /0.25 /∞ /0 (BF/DF) LWD 10 mm | Standard Outfit |
| 20x /0.4 /∞ /0 (BF/DF) LWD 5 mm | Standard Outfit |
| 50x /0.75 /∞ /0 (BF/DF) LWD 1.3 mm | Standard Outfit |
| 100x /0.9 /∞ /0 (BF/DF) LWD 0.7 mm | Standard Outfit |
| Viewing Head | |
| Siedentopf binocular viewing head, Inclined at 30°, Interpupillary 48-75 mm | Standard Outfit |
| Kohler Incident Light | |
| 12 V/ 50 W halogen light, center and brightness adjustable | Standard Outfit |
| Polarizer and analyzer | Standard Outfit |
| DIC | Optional |
| Built-in green, blue, yellow, gray and ground glass | Standard Outfit |
| Focusing | |
| Coaxial coarse and fine adjustment, fine division 2µm | Standard Outfit |
| Nosepiece | |
| Backward quintuple nosepiece | Standard Outfit |

| Stage | |
|--|-----------------|
| Double layer mechanical stage 226x178 mm, Moving range 40 mmx40 mm | Standard Outfit |
| Stage Φ20, Φ30, teardrop | Standard Outfit |
| Accessories | |
| Photo/Video attachment | Optional |
| Micrometer scale 0.01mm | Standard Outfit |
| Power Supply | |
| AC110/220 V ± 10%, 50/60 Hz | Standard Outfit |
| Package Size | |
| 730x350x550 mm | Standard Outfit |
| Gross Weight | |
| 18kg | Standard Outfit |



Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@centrifugen.com | Website: centrifugen.com