# INTEGRATED OR LAMP OPL48-14



# **INTEGRATED OR LAMP OPL48-14**

Shadowless operation lamp is suitable for the requirement of various operation conditions and it is ideal operating lighting equipment for modern operation rooms. Based on trichromatic theory, the light is closer to natural light, which is suitable for medical workers to distinguish the color of vascular tissue, nerve ending and so on. Adapts US blue cold light coating technology, the optical filter could effectively filter ultraviolet rays from the spectrum.

Used in Medical unit, Surgery, Operation theatre.

Also known as Integrated surgical Light, Integrated OT light.

### **OPL48-14** INTEGRATED OR LAMP

The imported switch power supply is adopted to control the voltage, making the work voltage permanently stable

The removable handle sheath can be disinfected at the high temperature of 135°C

The special radiation filer reducing the heat to the minimum level

The depolished panel is made of imported material makes the light rays softer

The multi-flake retroreflector made of imported aluminum sheet, has the feature of no coating film and never fading

Light adjustment circuit adopts CPU control, enabling increase or decrease of illumination and boasting brightness memory

One lamp holder with two bulbs enables automatic operation of the standby bulb in 1/2 second when the main bulb malfunctions, and it has indicators for damage of main or standby bulb

Imported lamp receptable, Tungsten halogen bulbs of international brand are adopted with average service more than 1500 hrs.

AC/DC, may satisfy when the power failure continues the surgery. (AC / DC type)



### **SPECIFICATIONS**

Model	OPL48-14
Illumination	160,000 Lux
Adjusting range of illuminance	10-100%
Spot diameter (D50-D10)	130-350 mm
L1+L2 Depth of illumination	140 cm
Color rendering Index (Ra)	≥97
Color Temperature (K)	3600K-5500K (±500K) variable
Average bulb life (hours)	100,000 h
Power supply	220 V 50 Hz
Power of bulb	1 W x N 128
Light focus system	Manual
Input power	160 W
Ceiling height for installation (cm)	2.8 m

2



## Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@centrifugen.com | Website: centrifugen.com