

# 4°C BLOOD BANK REFRIGERATOR REF23-1008



# 4°C BLOOD BANK REFRIGERATOR REF23-1008

Designed as an essential piece of equipment in the immunohematology department and provides safe and convenient storage of whole blood, blood components, reagents and ensures freshness and integrity of blood and blood components. Microprocessor integrated system provides excellent temperature accuracy and reliable performance.

Used in Immunohematology Department, Blood Bank, Laboratory, Research, Medical, Pharmaceutical.

Also known as Laboratory Blood Bank Refrigerator.

## REF23-1008 4°C BLOOD BANK REFRIGERATOR

Microprocessor controlled forced-air cooling with electrical heat compensation system

Digital temperature display for upper and lower sections in chamber with 0.1°C resolution

Consistent cabinet temperature 2-6°C

High-tech integrated sensors to display and control temperature

Auto-defrost to remove moisture on cooling surface

Build-in backup battery to display temperature and to operate audible and visual alarm systems for up to 72 hours without ac power

Equipped with a complete temperature alarm system featuring audible buzzer and visible flashing light

Standard with laser printer

Standard with acrylic inner small door, for less affection on other room when one door open

Safety lock to prevent unauthorized access

Storage space designed for easy sorting of a variety of blood products



## SPECIFICATIONS

Model	REF23-1008
Capacity	1008 L
Temperature Range	4°C±1
Ambient Temperature	10~32 °C
Refrigerant	R134a, CFC free
Defrost Method	No Frost with heated glass door
Controller	Microprocessor Control with digital Display
Cooling Type	Forced air cooling
Compressor	Secop/1
Evaporator	Finned evaporator
Evaporator material	Copper pipe and aluminum fin
Condenser	Finned
Sensor	NTC
Alarms	High/low temperature, Power off, Temperature controller malfunction, Backup battery malfunction, Backup battery Alarm for power off (72h)
Insulation	PURF
Material	Inside: Stainless steel
Outside	
Color sprayed steel	Shelves

Drawers	Mode of Condenser
53.6 dB	Internal Size
1100x684x1325 mm	External Size
1220x878x1885 mm	Package Size
1300x960x2080 mm	Accessories
Caster, Test hole 1/25MM, Thermal printer	Optional Accessories
Temperature recorder	Weight
256 / 286 kg	Power consumption (kW.h/24h)
8.53 kWh/24hrs	Power
513 W	Power Supply

# ***Centrifugen***

## **Centrifugen**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [info@centrifugen.com](mailto:info@centrifugen.com) | Website: [centrifugen.com](http://centrifugen.com)