

BIOLOGICAL INDICATOR INCUBATOR



BIOLOGICAL INDICATOR INCUBATOR

Biological Indicator Incubator is supporting equipment for bio-indicator. It is small in size, less weight and is suitable for pressure steam sterilizer biological indicator, ethylene oxide sterilization biological indicator and other biological indicator sterilization, effect detection and cultivation.

Used in Environmental protection, Research institutes, University laboratories.

Also known as Laboratory Incubator.

INC51-100 BIOLOGICAL INDICATOR INCUBATOR

Unique designed. Small size, light weight, portable, and suits on various occasions.

LCD display. Temperature and time display simultaneously.

Auto fault detect and buzzer alarm. Temperature calibration function.

24V DC power supply input, low energy consumption. Built-in over-temperature protection device, safe and reliable.

Timing function. Time range from 0 to 999 min.

Variety of standard sample blocks for choice. Convenient for replacement. Block can be customized.



SPECIFICATIONS

Model	INC51-100
Temperature Range	RT+5°C~100°C
Temperature Accuracy	±0.5°C at 56°C
Display Accuracy	0.1°C
Time for Heating	≤6 min (20°C to 56°C)
Timer Range	1 sec~999 sec or 1 min~999 min
Overall Dimension (WxDxH)	110x156x92 mm
Weight	1 kg
Power	60 W
Power Supply	DC 24 V adapter

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS54430	Block A	15 x Φ10 mm
LS54442	Block B	12 x Φ12 mm
LS54454	Block C	6 x Φ15 mm
LS54466	Block D	6 x Φ16 mm
LS54478	Block E	18 x Φ 9 mm
LS54814	customized	

INC52 BIOLOGICAL INDICATOR INCUBATOR

- Designed for incubation of EO biological indicators
- Customized wells for placement of biological indicator vials
- Easy to set incubation temperature
- Aluminium blocks available to meet different experimental requirements



SPECIFICATIONS

Model	INC52-080	INC52-100
Temperature Range	RT+5-80°C	RT+5-100°C
Temperature Accuracy	0.35°C at 57°C	
Temperature Uniformity	0.5°C	
Temperature Resolution	0.1°C	
Time for Heating	≤6 min (20°C to 57°C)	
Timer Range	1 min-99h 59 min	
Overall Dimension (WxDxH)	110x150x80 mm	120x152x112 mm
Display	LCD	
Weight	0.5/1 kg	0.85/1.4 kg
Power	120 W	
Power Supply	240 V, 60 Hz	

OPTIONAL ACCESSORIES

Accessory Code	Name	Description	For Models
LS52989	Block C	6xΦ15 mm	All
LS53001	Block D	6xΦ16 mm	All
LS53013	Block E	24xΦ8.8 mm	All
LS53025	Block F	18xΦ9 mm	All
LS53049	Block B	15xΦ12 mm	All
LS54430	Block A	15 x Φ10 mm	INC52-080
LS53037	Block A	15xΦ10 mm	INC52-100



INC52-080



INC52-100

INC53-057 BIOLOGICAL INDICATOR INCUBATOR

Compact, fits in the palm of your hand
LCD display. It is easy to setup and use
Different kinds of aluminum blocks are available
Clear cover ensures temperature uniformity
Portable, Optional 24V adapter



SPECIFICATIONS

Model	INC53-057
Temperature Accuracy	0.35°C at 57°C
Temperature Control Accuracy	±0.5°C
Display Accuracy	0.1°C
Time for Heating	≤6 min (20°C to 57°C)
Timer Range	1 min-99 h 59 min
Overall Dimension (WxDxH)	120x152x112 mm

OPTIONAL ACCESSORIES

Accessory Code	Name	Description
LS53257	Block	Ø10 mm X 15 tube Block
LS53269	Block	Ø12 mm X 12 tube Block
LS53281	Block	Ø15 mm X 6 tube Block
LS53293	Block	Ø16 mm X 16 tube Block
LS53305	Block	Ø9 mm X 24 tube Block

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com