# CO2 INCUBATOR WATER JACKETED



# CO2 INCUBATOR WATER JACKETED

Water jacketed CO2 incubators are ideal for cell culture applications. These are designed to provide uniform temperatures and highly stable CO2 environments that are necessary to prevent shocks to cells. Precisely controlled, accurate, pure environment throughout the culturing process is maintained. High precise gas sensor is applied with automatic start function. These incubators are an ideal solution for labs involved with potential power disruption or significant ambient temperature fluctuations affecting the integrity of their cultures.

Used in Tissue Engineering, Vitro fertilization, Cell Culturing, Tissue culturing, Mammalian cell research, Oncology studies..

Also known as Laboratory CO2 Incubator Water Jacketed.

## **INCA2-185TCD** WATER JACKETED CO2 INCUBATOR (TCD)

Microprocessor temperature and CO2 controller

Water reservior volume: 3L

Alarms: Power interruption, High/Low temperature, CO2 deviation, low RH programmable alarm, Door ajar, Independent over heat protection

RS232 interface

Type 304 Stainless steel shelves



### **SPECIFICATIONS**

| Model                      | INCA2-185TCD                               |
|----------------------------|--|
| Capacity                   | 185 L                                      |
| Water Jacket Volume        | 43.5 L                                     |
| Temperature Range          | 5°C above ambient temperature to 55°C      |
| Temperature Stability      | ±0.1°C                                     |
| Temperature Uniformity     | ±0.2°C                                     |
| Temperature Sensors        | PT1000                                     |
| CO2 Range                  | 0-20%                                      |
| CO2 Stability              | ±0.1%                                      |
| CO2 Sensor                 | Thermal conductivity / IR                  |
| CO2 Inlet Pressure         | 0.1 Mpa                                    |
| Interior                   | Type 304, mirror finish, stainless steel   |
| Exterior                   | Cold-rolled steel, powder coated           |
| Internal Dimention (WxDxH) | 544x504x681 mm                             |
| Overall Dimension (WxDxH)  | 655x656x1030 mm                            |
| Shelves                    | 3 standard, 11 maximum                     |
| Weight                     | 110 kg                                     |
| Power                      | 430 W                                      |
| Power Supply               | 220V/50Hz (standard), 110V/60Hz (Optional) |



### Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA Email: info@centrifugen.com | Website: centrifugen.com