

WATER CHILLER



WATER CHILLER

Water chiller is a device used to lower the temperature of water. Water chiller use water as a refrigerant instead of toxic chemicals. This makes them safer for people who have contact with them. Water chiller are overall more efficient. Used in Biotechnology, Laser, Analytical, Automotive, Packaging, Injection Molding, Die Cutting, Food, Beverage, Chemical, Machine tool, Semi-conductor. Also known as Laboratory Water Chiller.

CHI11 WATER CHILLER

The well-known product spleen compressor, high-efficiency shell and tube condenser, evaporator combination, super refrigeration, power saving PID microcomputer full-function control, easy to operate, can accurately control the water temperature within 3°C~35°C.

Unique new design stainless steel opening Type thermal insulation water tank, easy to clean and repair, reasonable internal pipeline layout, effectively reducing energy consumption.

Copper pipes are welded with Smick L30345% silver electrode, with high density and long life.

With current overload protection, high and low voltage switch, delay protection, over temperature protection, antifreeze, abnormal indication system.



SPECIFICATIONS

Model	CHI11-008	CHI11-014	CHI11-023	CHI11-029
Freezing capacity				
kw	8.7 kw	14.5 kw	23.2 kw	29 kw
kcal/h	7482 kcal/h	12470 kcal/h	19952 kcal/h	-
btu/h	29684.4 btu/h	49474 btu/h	79158.4 btu/h	-
Compressor				
Output power	2.2 kw	3.7 kw	6 kw	-
hp	3 hp	5 hp	4x2 hp	-
Weight	1.5 kg	2.5 kg	3.8 kg	-
Power	-	-	-	5hpX2
Refrigerant				
Control mode	Thermal expansion valve			-
Type	R22 (R407C optional)			-
Evaporator(Type)	Tube-in-shell			-
Condensor(Water Chiller)				
Type	Tube-in-shell			Tube-in-shell Condensor
Cooling water flow	35	60	95	-
In/out pipe	1 inch	1 v 2 inch		-
Water tank capacity	60 L		120 L	
Pump				
Type	Stainless steel centrifugal pump			-
Power kw	0.37 kw		0.75 kw	1 hp

Flow rate	88 l/min		115 l/min	
Working pressure	2 bar			-
Chilled wateroutlet	1 inchx1 1 " x1	1 inch x1	1 v 2 inchx1	-
Pipe coupling				
Chilled water inlet	1 inchx1		1 v 2 inchx1	-
Water tank drainage port	1/2 inch			-
Dimension(LXWXH) mm	1080x570x940 mm		1180x800x1030 mm	
Weight	180 kg	210 kg	300 kg	370 kg
Power	3 ph-380 V/50 Hz (220 V/400 V/415 V/440 V 50 Hz/60 Hz)			-
Temperature	5-35 °C			-
Tolerance	± 0.5 °C (± 1 °C at low load)			-
Safety protections	High and low pressure controller/anti-freezing switch/overload of pump and compressor protection/overheat protection/delayed protection			-

Model	CHI11-029W	CHI11-033	CHI11-033W	CHI11-044
Freezing capacity				
kw	29 kw	-	33.3 kw	44 kw
kcal/h	24940 kcal/h	-	28638 kcal/h	-
btu/h	98948 btu/h	-	113619.6 btu/h	-
Compressor				
Output power	7.5 kw	-	9 kw	-
hp	5x2 hp	-	6x2 hp	-
Weight	5 kg	-	7 kg	-
Power	-	6hpx2	-	5hpx3
Refrigerant				
Control mode	Thermal expansion valve	-	Thermal expansion valve	-
Type	R22 (R407C optional)	-	R22 (R407C optional)	-
Evaporator(Type)	Tube-in-shell	-	Tube-in-shell	-
Condensor(Water Chiller)				
Type	Tube-in-shell	Tube-in-shell Condensor	Tube-in-shell	Tube-in-shell Condensor
Cooling water flow	119	-	130	-
In/out pipe	2 inch	-	2 inch	-
Water tank capacity	120 L	-	160 L	200 L
Pump				
Type	Stainless steel centrifugal pump	-	Stainless steel centrifugal pump	-
Power kw	0.75 kw	1 hp	0.75 kw	2 hp
Flow rate	115 l/min			-
Working pressure	2 bar	-	2 bar	-
Chilled wateroutlet	1 v 2 inchx1	-	2 inch x1	-
Pipe coupling				
Chilled water inlet	1 v 2 inch x1	-	2 inch x1	-
Water tank drainage port	1/2 inch	-	1/2 inch	-
Dimension(LXWXH) mm	1180x800x1030 mm	-	1360x850x1220 mm	-
Weight	330 kg	-	430 kg	700 kg
Power	3 ph-380 V/50 Hz (220 V/400 V/415 V/440 V 50 Hz/60 Hz)	-	3 ph-380 V/50 Hz (220 V/400 V/415 V/440 V 50 Hz/60 Hz)	-
Temperature	5-35 °C	-	5-35 °C	-

Tolerance	± 0.5 °C (± 1 °C at low load)	-	± 0.5 °C (± 1 °C at low load)	-
Safety protections	High and low pressure controller/anti-freezing switch/overload of pump and compressor protection/overheat protection/delayed protection	-	High and low pressure controller/anti-freezing switch/overload of pump and compressor protection/overheat protection/delayed protection	-

Model	CHI11-044W	CHI11-057	CHI11-069	CHI11-090
Freezing capacity				
kw	44 kw	57.5 kw	69.8 kw	90 kw
kcal/h	-	-	-	-
btu/h	-	-	-	-
Compressor				
Output power	-	-	-	-
hp	-	-	-	-
Weight	-	-	-	-
Power	7.5hpx2	10hpx2	12.5hpx2	10hpx3
Refrigerant				
Control mode	-	-	-	-
Type	-	-	-	-
Evaporator(Type)	-	-	-	-
Condensor(Water Chiller)				
Type	Tube-in-shell Condensor			
Cooling water flow	-	-	-	-
In/out pipe	-	-	-	-
Water tank capacity	200 L	250 L		265 L
Pump				
Type	-	-	-	-
Power kw	2 hp	3 hp		
Flow rate	-	-	-	-
Working pressure	-	-	-	-
Chilled wateroutlet	-	-	-	-
Pipe coupling				
Chilled water inlet	-	-	-	-
Water tank drainage port	-	-	-	-
Dimension(LXWXH) mm	-	-	-	-
Weight	700 kg	750 kg	800 kg	950 kg
Power	-	-	-	-
Temperature	-	-	-	-
Tolerance	-	-	-	-
Safety protections	-	-	-	-

Model	CHI11-090W	CHI11-117	CHI11-117W	CHI11-142
Freezing capacity				
kw	90 kw	117.5 kw		142 kw
kcal/h	77400 kcal/h	-	101050 kcal/h	122120 kcal/h
btu/h	307080 btu/h	-	400910 btu/h	484504 btu/h
Compressor				
Output power	22 kw	-	30 kw	37.5 kw

hp	10x3 hp	-	20x2 hp	25x2 hp
Weight	17 kg	-	20 kg	34 kg
Power	-	10hpx4	-	-
Refrigerant				
Control mode	Thermostatic expansion valve	-	Thermostatic expansion valve	
Type	R22 (R407C optional)	-	R22 (R407C optional)	
Evaporator(Type)	Tube-in-shell	-	Tube-in-shell	
Condensor(Water Chiller)				
Type	Tube-in-shell	Tube-in-shell Condensor	Tube-in-shell	
Cooling water flow	350	-	500	600
In/out pipe	3 inch	-	3 inch	
Water tank capacity	265 L	330 L		350 L
Pump				
Type	Stainless steel centrifugal pump	-	Stainless steel centrifugal pump	
Power kw	2.2 kw	5 hp	3.75 kw	
Flow rate	315 l/min	-	367 l/min	400 l/min
Working pressure	2.2 bar	-	3 bar	
Chilled wateroutlet	2 v 2 inch x1	-	3 inch	
Pipe coupling				
Chilled water inlet	2 v 2 inch x1	-	3 inch	
Water tank drainage port	1 inch	-	1 inch	
Dimension(LXWXH) mm	1980x970x1430 mm	-	2870x1055x1740 mm	3260x1055x1740 mm
Weight	700 kg	1200 kg	1160 kg	1500 kg
Power	3 ph-380 V/50 Hz (220 V/400 V/415 V/440 V 50 Hz/60 Hz)	-	3 ph-380 V/50 Hz (220 V/400 V/415 V/440 V 50 Hz/60 Hz)	
Temperature	5-35 °C	-	5-35 °C	
Tolerance	± 0.5 °C (± 1 °C at low load)	-	± 0.5 °C (± 1 °C at low load)	
Safety protections	High and low pressure controller/anti-freezing switch/overload of pump and compressor protection/overheat protection/delayed protection	-	High and low pressure controller/anti-freezing switch/overload of pump and compressor protection/overheat protection/delayed protection	



CHI11-008



CHI11-014



CHI11-023



CHI11-029



CHI11-029W



CHI11-033



CHI11-033W



CHI11-044



CHI11-044W



CHI11-057



CHI11-069



CHI11-090



CHI11-090W



CHI11-117



CHI11-117W



CHI11-142

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com