

ELECTRIC OPERATION TABLE



ELECTRIC OPERATION TABLE

Biokel's electric operation table are cost effective, multi performance mobile operating table that meets the requirement of different surgeons. Easy-to-use electronic controls. Operation table equipped with a table top that rotates 180 degrees, and the chest plate, back plate, head plate, and leg plate on this table can all be easily adjusted, allowing for the ideal positioning of patients undergoing medical imaging tests.

Used in Medical unit, Surgery, Operation theatre, cardiovascular, pediatric, gynecology, abdominal, gall bladder, plastic surgery and more.

Also known as Electric surgical table, Electric OR Table, Electric operating table.

OPT28-0500 ELECTRIC OR TABLE

Material: Steel Powder Coated S.S, Color: Black



SPECIFICATIONS

Model	OPT28-0500
Backrest	-10°~75°, 500x480 mm
Height Adjustment	650/850 mm
Forward and back tilting	0~25°
Left tilt	0~18°
Right tilt	0~18°
Plate down folding	0~90°
Head rest	270x380 mm
Seat section	450x480 mm
Foot rest	200x533 mm
Table size	2100x480 mm
Dimension	2070Lx480Wx650/850H mm

OPT26-2000 ELECTRIC OR TABLE

Panel control and remote control, with battery can fit for 50 sets operating

The mattress is wrapped with imported artificial leather. High-density memory sponge is formed in one piece, with no seam

Imported LINAK motor without noise and with long life-span

The base seat and upright column covering are made of high quality 304 stainless steel which can be easily cleaned and sterilized

Foot treadle brake device which is easy for moving operating table

The leg part use spring gas control, separate leg part

It has the function of auto-restoration

One press to “^” or “v”



SPECIFICATIONS

Model	OPT26-2000
Table Length	2000±100 mm
Table Width	520±20 mm
Height Adjustment	(750~1000) ±50 mm
Trendelenburg	≥15°
Reverse trendelenburg	≥15°
Head board upwards	≥40°
Head board downwards	≥90°
Backboard upwards	≥60°
Backboard downwards	≥30°
Waist board lifting	100±20 mm
Leg board upwards	≥15°
Leg board downwards	≥90°
Leg board outwards	≥180°
Lumbar upper corner “^”	≤150°
Lumbar lower corner “v”	≤120°
Main Voltage AC	220V±22V, 50Hz±1Hz
Input Power VA	300±10%

OPT27-2000 ELECTRIC OR TABLE

The super low level design can enable doctor to conduct operation sitting by operating table.

The base seat and upright column covering are made of high quality 304 stainless steel which can be easily cleaned and sterilized

The bed surface adopts imported carbon plastic plate, which can fulfill the needs of X-ray examination, photography

The mattress is wrapped with quality artificial leather. High-density memory sponge is formed in one piece, with no seam

Various actions are controlled according to electric hydraulic working principle and by remote controller

Imported motor and solenoid valve

Imported sealing ring and is durable

Electrical braking device which is easy to moving operating table

Leg board controlled by gas spring



SPECIFICATIONS

Model	OPT27-2000
Table Length	2000±100 mm
Table Width	520±20 mm
Height Adjustment	(560~860) ±50 mm
Left tilt	≥20°
Right tilt	≥20°
Trendelenburg	≥20°
Reverse trendelenburg	≥18°
Head board upwards	≥50°
Head board downwards	≥90°
Backboard upwards	≥70°
Backboard downwards	≥20°
Waist board lifting	100±20 mm
Leg board upwards	≥15°
Leg board downwards	≥90°
Leg board outwards	≥180°
Lumbar upper corner "Λ"	≤160°
Lumbar lower corner "v"	≤105°
Main Voltage AC	220V±22V, 50Hz±1Hz
Input Power VA	500±10%

OPT25-2000 ELECTRIC OR TABLE

Electro-hydraulic mode of operation is adopted. Two control modes (hand-held remote controller and panel) are available to control various movements. MCU processing is used

Self-locking function is provided to avoid false triggering

Quality stainless steel 304 is used for table support, base plate, column shield and rails on both sides of the table, easy for cleaning and sterilization. Console supports the use of cast aluminium parts, never rust

The mattress is wrapped with imported artificial leather. High-density memory sponge is formed in one piece, with no seam

Quality carbon steel plate is used for the table top, which is convenient for X-ray photography

AC and DC can use at the same time

It has the function of auto-restoration

The table top can sliding

Electric braking device, convenient for shifting the operating table

One press to "Λ" or "V"



SPECIFICATIONS

Model	OPT25-2000
Table Length	2000±100 mm
Table Width	520±20 mm
Height Adjustment	(700~1150) ±50 mm
Left tilt	≥20°
Right tilt	≥20°
Trendelenburg	≥28°
Reverse trendelenburg	≥28°
Head board upwards	≥50°
Head board downwards	≥90°
Backboard upwards	≥75°
Backboard downwards	≥50°
Waist board lifting	100±20 mm
Leg board upwards	≥10°
Leg board downwards	≥90°
Leg board outwards	≥180°
Lumbar upper corner "Λ"	≤150°
Lumbar lower corner "v"	≤110°
Horizontal and longitudinal movement	300±30 mm
Main Voltage AC	220V±22V, 50Hz±1Hz
Input Power VA	400±10%

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com