

TURBIDITY METER



TURBIDITY METER

Used in Water treatment plants.
Also known as Turbidimeter.

MET71-200 TURBIDITY METER



Product Image Coming Soon

SPECIFICATIONS

Model	MET71-200
Measuring Unit	
Range	(0 ~ 20.00) NTU, (20.0 ~ 200.0) NTU
Resolution	0.01NTU, 0.1NTU, 1NTU
Accuracy	≤ ±8 %
Fluctuation	≤ ±1.0% FS/30 min
General	
Power Supply	AA Battery, AC Adapter 200-240 VAC input DC5V output
Dimension (mm) & Weight (kg)	100×220×80,0.8

MET71-240 TURBIDITY METER



Product Image Coming Soon

SPECIFICATIONS

Model	MET71-240
Measuring Unit	
Range	(0 ~ 20.00) NTU, (20.0 ~ 200.0) NTU
Accuracy	$\leq \pm 8\%$
Repeatability	$\leq 1.0\%$
Fluctuation	$\leq \pm 1.0\%$ FS/30xmin
General	
Power Supply	AC Adapter, 200-240 VAC input
Dimension (mm) & Weight (kg)	330×250×130, 2.5

MET71-232 TURBIDITY METER



Product Image Coming Soon

SPECIFICATIONS

Model	MET71-232
Measuring Unit	
Range	(0.000 ~ 20.00) NTU, (20.01 ~ 200.0) NTU, (200 ~ 2000) NTU, (2001 ~ 4000) NTU
Accuracy	$\leq \pm 6\%$
Repeatability	$\leq 0.5\%$
Fluctuation	$\leq \pm 0.5\%$ FS/30xmin
General	
Power Supply	AC Adapter, 200-240 VAC input
Dimension (mm) & Weight (kg)	358×323×160, 8

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com