

COLORIMETER



COLORIMETER

Used in Paint and Varnish Industry, Food and Publishing Industry.

Also known as Philtre photometer, Photometer.

MET81-500 COLORIMETER



Product Image Coming Soon

SPECIFICATIONS

Model	MET81-500
Optical Geometry	8°/D
Standards compliant	CIE No.15, GB/T 3978
Sensor	Silicon Photoelectric Diode Array
Measuring Aperture	Φ 8 mm flat, Φ 4 mm sharp
Color Space	CIE LAB, LCh,XYZ, CIE RGB,CIE LUV
Observer	CIE 10° Standard observer
Illuminant	D65,A,C,D50,F2,F6,F7,F8,F10,F11,F12
Displayed Data	Chromaticity Values, Color Difference Values, Pass/Fail Result, Color Offset/Deviation Direction
Measurement Time	1.5 s
Repeatability	ΔE^*ab 0.03
Inter-instrument agreement	ΔE^*ab Within 0.4 (average value for measuring BCRA series II 12pcs palettes)
Size	205x67x80 mm
Weight	500 g
Battery Performance	Rechargeable Li-on Battery, 3.7V@3200 m A h
Lamp Life	5 years, more than 1.6 million measurements
Display	TFT Color 2.8inch@ (16:9)
Interface	USB
Data Storage	Standard: 100, Sample: 20000
Operating Environment	0~40 °C (32~104 °F)
Storage Environment	- 20~50 °C (-4~122 °F)
PC Software	CQCS3 software
Standard Accessories	Power adapter, manual, quality management software (official website download), USB cable, wristband
Optional Accessories	Micro Printer, Powder Test Box

MET81-400 COLORIMETER



Product Image Coming Soon

SPECIFICATIONS

Model	MET81-400
Optical Geometry	45°/0°
Standards compliant	CIE No.15, GB/T 3979
Sensor	Silicon Photoelectric Diode Array
Measuring Aperture	Φ 20 mm
Color Space	CIE LAB,XYZ, LCh
Observer	CIE 10° Standard observer
Illuminant	D65
Displayed Data	Chromaticity Values, Color Difference Values, Pass/Fail Result, Color Offset/Deviation Direction
Measurement Time	1.5 s
Repeatability	ΔE^*ab Within 0.08 (average value for 30 times)
Inter-instrument agreement	ΔE^*ab Within 0.4 (average value for measuring BCRA series II 12pcs palettes)
Size	205x67x80 mm
Weight	About 400g(including battery)
Battery Performance	Rechargeable Li-on Battery, 3.7 V @ 3200 mAh
Lamp Life	5 years, more than 1.6 million measurements
Display	TFT Color 2.8inch@ (16:9)
Interface	USB
Data Storage	Standard: 100, Sample: 20000
Operating Environment	1~40 °C (32~104 °F)
Storage Environment	- 20~50 °C (-4~122 °F)
PC Software	CQCS3 software
Standard Accessories	Power adapter, manual, quality management software (official website download), USB cable, wristband
Optional Accessories	Micro Printer, Powder Test Box

MET81-065 COLORIMETER



Product Image Coming Soon

SPECIFICATIONS

Model	MET81-065
Optical Geometry	8°/D
Standards compliant	CIE No.15, GB/T 3980
Sensor	Silicon Photoelectric Diode Array
Measuring Aperture	Φ 4 mm flat, Φ 4 mm sharp
Color Space	CIE LAB, Lch,XYZ
Observer	CIE 10° Standard observer
Illuminant	D65
Displayed Data	Chromaticity Values, Color Difference Values, Pass/Fail Result, Color Offset/Deviation Direction
Measurement Time	1.5 s
Repeatability	ΔE^*_{ab} 0.08
Inter-instrument agreement	ΔE^*_{ab} Within 0.4 (average value for measuring BCRA series II 12pcs palettes)
Size	205x67x80 mm
Weight	About 400g(including battery)
Battery Performance	Rechargeable Li-on Battery, 3.7 V @ 3200 mAh
Lamp Life	5 years, more than 1.6 million measurements
Display	TFT Color 2.8inch@ (16:9)
Interface	USB
Data Storage	Standard: 100, Sample: 20000
Operating Environment	1~40 °C (32~104 °F)
Storage Environment	- 20~50 °C (-4~122 °F)
PC Software	CQCS3 software
Optional Accessories	Micro Printer, Powder Test Box

MET81-040 COLORIMETER



Product Image Coming Soon

SPECIFICATIONS

Model	MET81-040
Optical Geometry	8°/D
Standards compliant	CIE No.15, GB/T 3981
Sensor	Silicon Photoelectric Diode Array
Measuring Aperture	Φ 4 mm
Color Space	CIE LAB, LCh
Observer	CIE 10° Standard observer
Illuminant	D65
Displayed Data	Chromaticity Values, Color Difference Values, Pass/Fail Result, Color Offset/Deviation Direction
Measurement Time	1.5 s
Repeatability	ΔE^*_{ab} 0.03
Inter-instrument agreement	ΔE^*_{ab} Within 0.4 (average value for measuring BCRA series II 12pcs palettes)
Size	206x67x80 mm
Weight	About 400g(including battery)
Battery Performance	Rechargeable Li-on Battery, 3.7 V @ 3200 mAh
Lamp Life	5 years, more than 1.6 million measurements
Display	TFT Color 2.8inch@ (16:9)
Interface	USB
Data Storage	Standard: 100, Sample: 10000
Operating Environment	1~40 °C (32~104 °F)
Storage Environment	- 20~50 °C (-4~122 °F)
Standard Accessories	Power adapter, manual, quality management software (official website download), USB cable, wristband
Optional Accessories	Micro Printer, Powder Test Box

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com